

## PCL MK3 Airline Gauges

### ALG3H03 & ALG3H04

- Latest in a long line of thoroughbreds, styled for the 90's and beyond, with 'no compromise' good looks and durability
- Designed to meet EC standards
- Constructed in lightweight, die cast aluminium
- Impact absorbing rubber bumper and magnified linear scale
- Supplied complete with a certificate of calibration and full operating instructions
- Approved to 86/217/EC Certificate No C2228 (UK92) (bar scale only)

## PCL Tyre Shop Airline Gauges

### ALG3H05, ALG3H06 & ALG3H061

- Tyre shop model features 1.8m (6ft) or 2.7m (9ft) connection hoses
- Twin clip-on connector (open end)
- Specially made for tyre shops
- Longer hose simplifies connection to the tyre valve
- Safe working distance between the fitter and tyre

## PCL High Pressure Airline Gauges

### ALG5H04, ALG5A02, ALG5A03

- Special high pressure gauge
- Calibrated from 45 to 300 lbf/in<sup>2</sup> in 5 lbf/in<sup>2</sup> increments, and 3 to 21 bar increments



Technical Spec.	ALG3H03	ALG3H04	ALG3H05	ALG3H06	ALG3H061	ALG5H04	ALG5A02	ALG5A03
Length x height x width (mm)	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50	270 x 90 x 50
Weight (kg)	1.02	0.9	1.13	1.35	1.35	1.13	1.13	1.13
Hose (m)	0.53	0.53	1.8	2.7	2.7	2.18	2	2
Pressure	0-138 psi (0-9.6 bar)	0-138 psi (0-9.6 bar)	0-138 psi (0-9.6 bar)	0-138 psi (0-9.6 bar)	0-138 psi (0-9.6 bar)	45-300 psi (3-21 bar)	45-300 psi (3-21 bar)	45-300 psi (3-21 bar)
Connector	Twin hold-on	Single clip-on	Twin clip-on	Twin clip-on	Single clip-on	Single clip-on	8V1 screw-on	12V1 screw-on

## A6225 - Dial Type Airline Gauge



- For motor vehicles, cycles, inflatable dinghies, lilos etc.
- Deflation facility
- Positive grip lock-on connector
- Heavy duty 200 psi reinforced hose
- Gauge reading 140 psi
- Display packed

## PCL Dial Type Airline Gauge



- Designed for use in tyre bays and workshops
- High visibility, accuracy and durability
- Manufactured to EC standards
- Constructed lightweight, die cast aluminium
- Impact absorbing rubber bumper
- Supplied complete with an individual certificate of calibration and full operating instructions
- Gauge approved to 86/217/EC (bar scale only)

Technical Spec.	ALG7H03	ALG7H04	ALG7H041	ALG7H05	ALG7H06	ALG7H08
Length x height x width (mm)	200 x 80 x 110	200 x 80 x 110	200 x 80 x 110	200 x 80 x 110	200 x 80 x 110	200 x 80 x 110
Weight (kg)	1.0	1.0	1.0	1.0	1.0	1.0
Hose (m)	0.53	1.8	2.7	1.8	2.7	0.53
Pressure	0-140 psi (0-10 bar)	0-140 psi (0-10 bar)	0-140 psi (0-10 bar)	0-140 psi (0-10 bar)	0-140 psi (0-10 bar)	0-140 psi (0-10 bar)
Connector	Twin hold-on	Single clip-on	Single clip-on	Twin clip-on	Twin clip-on	Euro style single clip-on
Gauge diameter	70	70	70	70	70	70