

AUTO CHISELERS

NPK range of chisellers makes this an all purpose tool, capable of functioning superbly in any difficult parts of the chassis or body.



NBH-400
With Retainer Spring



NBH-600A
Built-in Power Regulator
With Retainer Spring

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Capacity				Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	Duralumin		Steel			mm	in	mm	in	mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
	mm	in	mm	in														
NBH-400	6.4	1/4	4.8	3/16	1,600	13	33/64	95	3 3/4	223	8 ²⁵ /32	1.4	3.1	1/4	9.5	3/8	0.11	3.9
NBH-600A	8	5/16	6.4	1/4	1,500	19	3/4	68	2 ¹¹ /16	245	9 ²¹ /32	2.0	4.4	1/4	9.5	3/8	0.16	5.7

Specifications are subject to change without notice.

SAW/FILE

NPK's original design of dual action device gives remarkable cutting speed. The rubber lined lever transmits the long infrared rays to the hand, reducing fatigue.

SAW



AS-22A

FILE



AS-22AF

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Max. Sheet Thickness Mild Steel		Free Frequency Per Minute	Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	mm	in		mm	in	kg	lb		mm	in	m ³ /min	ft ³ /min
AS-22A	1.5	1/16	10,000	212	8 ¹¹ /32	0.6	1.3	1/4	6.3	1/4	0.25	8.8
AS-22AF	—	—	6,500	187	7 ²³ /64	0.6	1.3	1/4	6.3	1/4	0.11	3.9

Specifications are subject to change without notice.

DIA CUTTERS

Dia Cutter can realize speedy cutting and trimming work. It has many applications on automotive repair, window frame manufacturing, sheet metal industries and fiber glass factories.



DAC-11

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Capacity (Wheel Size)		Free Speed Approx.	Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption		
				rpm	mm	in	kg		lb	mm	in	mm	in
	mm	in											
DAC-11	54×1.0×10		13,000	298	11 ²³ /32	1.7	3.7	1/4	6.3	1/4	0.45	15.9	

Specifications are subject to change without notice.