

## CONCRETE BREAKERS

Forged body breakers deliver powerful demolishing and ensure longer life.

**Model CB-15A:** especially suited for breaking up comparatively thin-layered concrete.

**Model CB-20A:** a general purpose machine.

**Model CB-30A:** a heavy duty purpose machine.

### CB-15A

Cap Chisel Holder



### CB-20A

Cap Chisel Holder



### CB-30A

Cap Chisel Holder



## SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm<sup>2</sup>,85psi)

Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	min <sup>-1</sup>	mm	in	mm	in	mm	in	kg	lb	G	mm	in	m <sup>3</sup> /min	ft <sup>3</sup> /min
CB-15A	1,400	35	1 3/8	115	4 17/32	477	18 25/32	15	33	1	19.0	3/4	0.9	31.8
CB-20A	950	38	1 1/2	165	6 1/2	555	21 27/32	20	44	1	19.0	3/4	1.2	42.4
CB-30A	850	45	1 9/16	165	6 1/2	595	23 7/16	29	63.8	1	19.0	3/4	1.3	45.9

Specifications are subject to change without notice.

## DIGGER

The tool is light in weight and easy to operate for excavation and demolition.



DIG-9

## SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm<sup>2</sup>,85psi)

Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	min <sup>-1</sup>	mm	in	mm	in	mm	in	kg	lb	Rc or NPT	mm	in	m <sup>3</sup> /min	ft <sup>3</sup> /min
DIG-9	1,500	42.8	1 11/16	63.5	2 1/2	489	19 1/4	8.8	19.4	3/8	12.7	1/2	1.1	38.8

Specifications are subject to change without notice.

## HYDRAULIC HAND BREAKERS



H-30



H-55

## SPECIFICATIONS

Recommended Oil Pressure 14MPa (140kgf/cm<sup>2</sup>,1990psi)

Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Working Oil Pressure			Oil Flow	Gas Pressure			Hose Size		Chisel Shank	
	min <sup>-1</sup>	mm	in	mm	in	mm	in	kg	lb	MPa	kgf/cm <sup>2</sup>	psi	ℓ/min	MPa	kgf/cm <sup>2</sup>	psi	mm	in	mm	in
H-30	1,460-1,800	28, 34	1.102, 1.339	22	7/8	556	21 7/8	16	35.2	8-10	80-100	1,140-1,420	15-20	1.8	18	256	12.7	1/2	22.2	7/8
H-55	900-1,300	35, 41	1.378, 1.614	68	2 11/16	647	25 15/32	25	55	9-11	90-110	1,280-1,560	20-30	2.0	20	284	12.7	1/2	31.8	1 1/4

Specifications are subject to change without notice.