

Die grinders are suitable for precise, delicate finishing as required in handling small points and burrs.

REAR EXHAUST TYPE

Low sound level Exhaust noise is cut by approx. 20~30%



RG-55



RG-10



RG-16AK



RG-16AKLW



RG-25



RG-25LW



RG-38A



RG-38AS
(Steel Housing)



RG-38BSLW
(Steel Housing)



RG-38ASLW
(Steel Housing)




RG-38AL




RG-38ASL
(Steel Housing)

OPTIONAL COLLET CHUCK

Model No.	Collet Size 3mm	Collet Size 1/8"	Collet Size 1/4"
RG-16AK	○	○	—
RG-16AKLW	○	○	—
RG-25	○	○	—
RG-25LW	○	○	—
RG-38A	○	○	○
RG-38AS	○	○	○
RG-38AL	○	○	○
RG-38ASL	○	○	○
RG-38ASLW	○	○	○
RG-38BSLW	○	○	○



SAFETY-LEVER TYPE



- ① Push the lever down, and
- ② Grip it

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm², 85psi)

Type	Model No.	Capacity (Wheel Size)		Collet Size	Max. Free Speed	Overall Length Approx.		Net Weight Approx.		Max. Output Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
		mm	in			mm	in	kg	lb	kw	ps		Rc or NPT	mm	in	m ³ /min
Grip	RG-55	10	13/32	3	60,000	168	6 5/8	0.16	0.35	0.13	0.18	1/8	6.3	1/4	0.15	5.3
	RG-10	12	1/2	3	50,000	165	6 1/2	0.22	0.48	0.11	0.15	1/8	6.3	1/4	0.2	7.1
	RG-38A	25	1	6	22,000	165	6 1/2	0.6	1.3	0.33	0.45	1/8	9.5	3/8	0.45	15.9
	RG-38AS	25	1	6	22,000	165	6 1/2	0.75	1.7	0.33	0.45	1/4	9.5	3/8	0.45	15.9
Lever	RG-16AK	16	5/8	6	35,000	177	6 31/32	0.4	0.88	0.24	0.32	1/4	6.3	1/4	0.25	8.8
	RG-25	20	13/16	6	30,000	176	6 15/16	0.52	1.1	0.32	0.44	1/4	6.3	1/4	0.4	14.1
	RG-38AL	25	1	6	22,000	172	6 25/32	0.7	1.5	0.33	0.45	1/4	9.5	3/8	0.45	15.9
	RG-38ASL	25	1	6	22,000	172	6 25/32	0.7	1.5	0.33	0.45	1/4	9.5	3/8	0.45	15.9
Safety Lever	RG-16AKLW	16	5/8	6	35,000	177	6 31/32	0.4	0.88	0.24	0.32	1/4	6.3	1/4	0.25	8.8
	RG-25LW	20	13/16	6	30,000	176	6 15/16	1.1	2.4	0.32	0.44	1/4	6.3	1/4	0.4	14.1
	RG-38ASLW	25	1	6	22,000	172	6 25/32	0.7	1.5	0.33	0.45	1/4	9.5	3/8	0.45	15.9
	RG-38BSLW	25	1	6	19,000	203	8	0.7	1.5	0.29	0.4	1/4	9.5	3/8	0.45	15.9

Specifications are subject to change without notice.