

## NON REVERSIBLE TYPE

The compact designed drills assure best possible drilling performance. Chuck is available at extra cost.



**NRD-6SA**  
Tapper Type  
**NRD-6SA(T)**  
Thread Type



**NRD-6PB**  
Tapper Type  
**NRD-6PB(T)**  
Thread Type



Thread Type



**NRD-10P**  
Tapper Type  
**NRD-10P(T)**  
Thread Type



**NRD-12PA**  
Tapper Type  
Built-in Speed Regulator  
**NRD-12PA(T)**  
Thread Type

## SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm<sup>2</sup>,85psi)

Model No.	Drilling Capacity		Jacobs Chuck		Free Speed Approx.	Overall Length Approx.		Net Weight Approx.		Spindle Offset Approx.		Max.Output		Air Inlet Thread	Hose Size		Average Air Consumption	
	mm	in	No	Thread	rpm	mm	in	kg	lb	mm	in	kw	ps	Rc or NPT	mm	in	m <sup>3</sup> /min	ft <sup>3</sup> /min
NRD-6SA	6.5	1/4	1	—	2,800	166	6 <sup>17</sup> / <sub>32</sub>	0.8	1.8	20.6	13 <sup>13</sup> / <sub>16</sub>	0.37	0.5	1/4	6.3	1/4	0.5	17.7
NRD-6SA(T)	6.5	1/4	—	3/8-24UNF	2,800	166	6 <sup>17</sup> / <sub>32</sub>	0.8	1.8	20.6	13 <sup>13</sup> / <sub>16</sub>	0.37	0.5	1/4	6.3	1/4	0.5	17.7
NRD-6PB	6.5	1/4	1	—	2,400	149	5 7/8	0.8	1.8	20.5	13 <sup>13</sup> / <sub>16</sub>	0.37	0.5	1/4	6.3	1/4	0.5	17.7
NRD-6PB(T)	6.5	1/4	—	3/8-24UNF	2,400	149	5 7/8	0.8	1.8	20.5	13 <sup>13</sup> / <sub>16</sub>	0.37	0.5	1/4	6.3	1/4	0.5	17.7
NRD-10P	10	3/8	2S	—	2,000	156	6 1/8	1.1	2.4	23	29 <sup>29</sup> / <sub>32</sub>	0.44	0.6	1/4	6.3	1/4	0.55	19.4
NRD-10P(T)	10	3/8	—	3/8-24UNF	2,000	156	6 1/8	1.1	2.4	23	29 <sup>29</sup> / <sub>32</sub>	0.44	0.6	1/4	6.3	1/4	0.55	19.4
NRD-12PA	13	1/2	6	—	1,500	187	7 3/8	2.6	5.7	34	11 <sup>11</sup> / <sub>32</sub>	0.53	0.72	1/4	9.5	3/8	0.65	23
NRD-12PA(T)	13	1/2	—	1/2-20UNF	1,500	187	7 3/8	2.6	5.7	34	11 <sup>11</sup> / <sub>32</sub>	0.53	0.72	1/4	9.5	3/8	0.65	23

Specifications are subject to change without notice.