

FLUX SCALING HAMMERS

Flux scaling hammers are easy handle and used for chipping stone, metal, concrete, brick and weld flux.



NF-00
Cap Chisel Holder



NF-0
Cap Chisel Holder



NF-19FA
Cap Chisel Holder



NF-1SH
Slide Ball Retainer



NF-25F
Slide Ball Retainer



NFB-25H
Slide Ball Retainer

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	min ⁻¹	mm	in	mm	in	mm	in	kg	lb	Re or NPT	mm	in	m ³ /min	ft ³ /min
NF-00	6,500	14	35/64	12	15/32	164	6 ¹⁵ / ₃₂	0.55	1.2	1/4	6.3	1/4	0.23	8.1
NF-0	5,500	18	45/64	18	23/32	177	6 ³¹ / ₃₂	0.8	1.8	1/4	6.3	1/4	0.23	8.1
NF-19FA	6,000	19	3/4	11	7/16	183	7 ³ / ₁₆	0.8	1.8	1/8	6.3	1/4	0.15	5.3
NF-1SH	4,800	22	55/64	22	7/8	187	7 ³ / ₈	0.94	2.1	1/4	6.3	1/4	0.25	8.8
NF-25F	4,800	25	63/64	17	11/16	225	8 ⁷ / ₈	1.5	3.3	1/4	9.5	3/8	0.2	7.1
NFB-25H	4,000	25.4	1	23	29/32	265	10 ⁷ / ₁₆	2.0	4.4	1/4	9.5	3/8	0.55	19.4

Specifications are subject to change without notice.

ENGRAVING HAMMERS

This small and light hammer is used to carve or chip stone.



NF-19FA
(For Finishing)



NF-25F
(For Rough Finishing)

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
	min ⁻¹	mm	in	mm	in	mm	in	kg	lb	Re or NPT	mm	in	m ³ /min	ft ³ /min
NF-19FA	6,000	19	3/4	11	7/16	183	7 ³ / ₁₆	0.8	1.8	1/8	6.3	1/4	0.15	5.3
NF-25F	4,800	25	63/64	17	11/16	225	8 ⁷ / ₈	1.5	3.3	1/4	9.5	3/8	0.2	7.1

Specifications are subject to change without notice.