

The one-hammer impact wrenches are mostly used in repair and garage work shops. These wrenches have distinguishing features of being light weight, low in air consumption, exceptionally powerful impacting per blow.

Built-in power regulator for easy adjustment.

9.5mm(3/8") Square Drive



NW-800
6 steps of power control
Stopper Pin Type Anvil



NW-800S
Stepless power control
Stopper Pin Type Anvil



SW-12
Stepless power control
Ring Type Anvil

12.7mm(1/2") Square Drive

Ring Type Anvil



NW-1200B
4 steps of power control
NW-1200B (2R)
Long Anvil



NW-1600HA
4 steps of power control
NW-1600HA (2R)
Long Anvil



NW-1600H-AT
4 steps of power control



NW-1600SA
4 steps of power control

19.05mm(3/4") Square Drive

Ring Type Anvil



NW-2000HA
4 steps of power control
NW-2000HA (4R)
Long Anvil

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm², 85psi)

Model No.	Capacity (Bolt Size)		Free Speed Approx. rpm	Overall Length Approx.		Net Weight Approx.		Spindle Offset Approx.		Square Shank Size		Air Inlet Thread Rc or NPT	Hose Size		Average Air Consumption	
	mm	in		mm	in	kg	lb	mm	in	mm	in		mm	in	m ³ /min	ft ³ /min
NW-800	10	3/8	7,000	128	5 1/32	1.25	2.8	22.5	7/8	9.5	3/8	1/4	6.3	1/4	0.1	3.5
NW-800S	10	3/8	8,000	178	7	1.1	2.4	25	1	9.5	3/8	1/4	6.3	1/4	0.1	3.5
SW-12	12	1/2	8,000	124	4 7/8	1.26	2.8	27	1 1/16	9.5	3/8	1/4	6.3	1/4	0.1	3.5
NW-1200B	14	9/16	7,000	174	6 27/32	1.8	4.0	28	1 3/32	12.7	1/2	1/4	6.3	1/4	0.1	3.5
NW-1200B(2R)	14	9/16	7,000	224	8 13/26	1.9	4.2	28	1 3/32	12.7	1/2	1/4	6.3	1/4	0.1	3.5
NW-1600SA	16	5/8	6,500	165	6 1/2	1.6	3.5	26	1 1/32	12.7	1/2	1/4	6.3	1/4	0.15	5.3
NW-1600HA	16	5/8	5,000	195	7 11/16	2.5	5.5	31.8	1 1/4	12.7	1/2	1/4	6.3	1/4	0.15	5.3
NW-1600HA(2R)	16	5/8	5,000	244	9 39/64	2.6	5.7	31.8	1 1/4	12.7	1/2	1/4	6.3	1/4	0.15	5.3
NW-1600H-AT	16	5/8	5,000	194	7 5/8	2.5	5.5	32.5	1 9/32	12.7	1/2	1/4	6.3	1/4	0.15	5.3
NW-2000HA	24	1 3/16	4,500	230	9 1/16	3.8	8.4	38	1 1/2	19.05	3/4	1/4	9.5	3/8	0.2	7.1
NW-2000HA(2R)	24	1 3/16	4,500	330	13	4.2	9.2	38	1 1/2	19.05	3/4	1/4	9.5	3/8	0.2	7.1

Specifications are subject to change without notice.

POWERFUL TYPE

19.05mm(3/4") Square Drive

Ring Type Anvil



NW-2800P
4 steps of power control
NW-2800P (4R)
Long Anvil

25.4mm(1") Square Drive

Pin Hole Type Anvil



NW-3500P
4 steps of power control

25.4mm(1") Square Drive

Pin Hole Type Anvil



NW-3500GA
4 steps of power control
NW-3500GA (6P)
Long Anvil



NW-4300GA
4 steps of power control
NW-4300GA (6P)
Long Anvil



Inside trigger
NW-4300GAU
4 steps of power control
NW-4300GAU(6P)
Long Anvil



NW-5000
4 steps of power control



NW-5000 (7P)
Long Anvil
4 steps of power control

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Capacity (Bolt Size)		Free Speed Approx.	Overall Length Approx.		Net Weight Approx.		Spindle Offset Approx.		Square Shank Size		Air Inlet Thread	Hose Size		Average Air Consumption	
	mm	in		rpm	mm	in	kg	lb	mm	in	mm		in	Rc or NPT	mm	in
NW-2800P	28	1 ³ / ₁₆	5,000	225	8 ²⁷ / ₃₂	5.0	11	41.5	1 5/8	19.05	3/4	3/8	9.5	3/8	0.25	8.8
NW-2800P(4R)	28	1 ³ / ₁₆	5,000	325	12 ²⁵ / ₃₂	5.4	11.9	41.5	1 5/8	19.05	3/4	3/8	9.5	3/8	0.25	8.8
NW-3500P	36	1 ³ / ₈	4,000	280	11	9.2	20.2	50	1 ³¹ / ₃₂	25.4	1	3/8	12.7	1/2	0.3	10.6
NW-3500GA	36	1 ³ / ₈	4,000	388	15 9/32	9.5	20.9	50	1 ³¹ / ₃₂	25.4	1	3/8	12.7	1/2	0.3	10.6
NW-3500GA(6P)	36	1 ³ / ₈	4,000	551	21 ¹¹ / ₁₆	10.5	23.1	50	1 ³¹ / ₃₂	25.4	1	3/8	12.7	1/2	0.3	10.6
NW-4300GA	42	1 ⁵ / ₈	4,000	453	17 ²⁷ / ₃₂	12.9	28.4	57	2 1/4	25.4	1	1/2	12.7	1/2	0.4	14.1
NW-4300GA(6P)	42	1 ⁵ / ₈	4,000	590	23 7/32	14.2	31.2	57	2 1/4	25.4	1	1/2	12.7	1/2	0.4	14.1
NW-4300GAU	42	1 ⁵ / ₈	4,000	453	17 ²⁷ / ₃₂	12.9	28.4	57	2 1/4	25.4	1	1/2	12.7	1/2	0.4	14.1
NW-4300GAU(6P)	42	1 ⁵ / ₈	4,000	590	23 7/32	14.2	31.2	57	2 1/4	25.4	1	1/2	12.7	1/2	0.4	14.1
NW-5000	52	2	3,000	430	16 ¹⁵ / ₁₆	16.5	36.3	62	2 7/16	25.4	1	1/2	12.7	1/2	0.45	15.9
NW-5000(7P)	52	2	3,000	610	24	18.0	39.6	62	2 7/16	25.4	1	1/2	12.7	1/2	0.45	15.9

Specifications are subject to change without notice.