

NEW KELENS

These are also scalers for removing scale and rust of ships or concrete dress in mixer agitators.



NKK-250 Grip Type
NKK-250L Lever Type



NKK-500 Grip Type
NKK-500L Lever Type



NKK-1000 Grip Type
NKK-1000L Lever Type



Lever Type

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Type	Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
		min ⁻¹	mm	in	mm	in	mm	in	kg	lb	Rc or NPT	mm	in	m ³ /min	ft ³ /min
Grip	NKK-250	4,000	25.4	1	23	29/32	514	20 1/4	3.4	7.5	3/8	9.5	3/8	0.45	15.9
	NKK-500	4,000	25.4	1	23	29/32	744	29 9/32	4.2	9.2	3/8	9.5	3/8	0.45	15.9
	NKK-1000	4,000	25.4	1	23	29/32	1,284	50 9/16	5.8	12.8	3/8	9.5	3/8	0.45	15.9
Lever	NKK250L	4,000	25.4	1	23	29/32	571	22 15/32	4.5	9.9	3/8	9.5	3/8	0.45	15.9
	NKK-500L	4,000	25.4	1	23	29/32	801	31 17/32	5.3	11.7	3/8	9.5	3/8	0.45	15.9
	NKK-1000L	4,000	25.4	1	23	29/32	1,341	52 25/32	6.9	15.2	3/8	9.5	3/8	0.45	15.9

Specifications are subject to change without notice.

SCALING HAMMERS

These scalers are used for removing old paint and rust.

Carbide tipped pistons available at extra cost, for use as concrete scrapers.



S-2
Grip Type



Lever Type

S-2L
Lever Type

S-2(C)
Carbide Tipped Piston Type

S-2L(C)
Carbide Tipped Piston Type



MS-30
Grip Type



Lever Type

MS-30(C)
Carbide Tipped Piston Type

MS-30L
Lever Type

MS-30L(C)
Carbide Tipped Piston Type

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Type	Model No.	Blows Per Minute	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Height Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
		min ⁻¹	mm	in	mm	in	mm	in	mm	in	kg	lb	Rc or NPT	mm	in	m ³ /min	ft ³ /min
Grip	S-2,(C)	8,000	30	1 3/16	15	29/32	490	19 9/32	100	3 15/16	2.1	4.6	3/8	9.5	3/8	0.4	14.1
	MS-30,(C)	7,000	22	55/64	10	19/32	326	12 27/32	86	3 3/8	3.2	7.0	3/8	12.7	1/2	0.55	19.4
Lever	S-2L,(C)	8,000	30	1 3/16	15	29/32	496	19 17/32	100	3 15/16	2.7	5.9	3/8	9.5	3/8	0.4	14.1
	MS-30L,(C)	7,000	22	55/64	10	13/32	332	13 1/16	86	3 3/8	3.8	8.4	3/8	12.7	1/2	0.55	19.4

Specifications are subject to change without notice.

STONE SCRAPER

The Stone Scraper is most suitable for surfacing concrete and stone.

NB-10
Grip Type
NB-10L
Lever Type



Lever Type

SCRAPER HEAD (OPTIONS)

Scraper Head	Code No.
9Teeth	17511270
16Teeth	17511280
25Teeth	17511290
36Teeth	17511300



9Teeth 16Teeth 25Teeth 36Teeth

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Type	Model No.	Blows Per Minute	Height Approx.		Net Weight Approx.		Air Inlet Thread	Hose Size		Average Air Consumption	
		min ⁻¹	mm	in	kg	lb	Rc or NPT	mm	in	m ³ /min	ft ³ /min
Grip	NB-10	2,500	210	8 1/4	10	22	3/8	9.5	3/8	0.35	12.4
Lever	NB-10L	2,500	210	8 1/4	10.6	23.2	3/8	9.5	3/8	0.35	12.4

Specifications are subject to change without notice.