

SAND RAMMERS

The sand rammers are easy to handle and ensure even sand compaction.

A necessary air implement for foundries, as an alternative. In the event of the steel butt causing damage to the mold. Use of the rubber butt is suggested.

Optional steel batt is available for all models.



B-00A



B-0A



B-1A

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Butt Diameter		Air Inlet Thread	Hose Size		Average Air Consumption	
	mm	in	mm	in	mm	in	kg	lb	mm	in	Rc or NPT	mm	in	m ³ /min	ft ³ /min
B-00A	18	45/46	60	2 ³ / ₈	337	13 9/32	2.1	4.6	40	1 ⁹ / ₁₆	3/8	9.5	3/8	0.2	7.1
B-0A	22	55/64	60	2 ³ / ₈	380	14 ³¹ / ₃₂	3.1	6.8	50	2	3/8	12.7	1/2	0.25	8.8
B-1A	25.4	1	110	4 ⁵ / ₁₆	502	19 3/4	5.4	11.9	64	2 ¹ / ₂	3/8	12.7	1/2	0.4	14.1

Specifications are subject to change without notice.



F-00



F-0



F-1



F-2



F-4

SPECIFICATIONS

Recommended Air Pressure 0.6MPa (6kgf/cm²,85psi)

Model No.	Piston Diameter		Piston Stroke Approx.		Overall Length Approx.		Net Weight Approx.		Butt Diameter		Air Inlet Thread	Hose Size		Average Air Consumption	
	mm	in	mm	in	mm	in	kg	lb	mm	in	Rc or NPT	mm	in	m ³ /min	ft ³ /min
F-00	18	45/64	60	2 3/8	390	15 ¹¹ / ₃₂	2.1	4.6	40	1 ⁹ / ₁₆	3/8	9.5	3/8	0.2	7.1
F-0	22	55/64	60	2 3/8	435	17 1/8	3.1	6.8	50	2	3/8	12.7	1/2	0.25	8.8
F-1	25.4	1	110	4 5/16	1,098	43 7/32	6.8	15.0	64	2 ¹ / ₂	1/2	12.7	1/2	0.4	14.1
F-2	32	1 ¹⁷ / ₆₄	120	4 ²³ / ₃₂	1,134	44 ²¹ / ₃₂	9.0	19.8	70	2 ³ / ₄	1/2	12.7	1/2	0.55	19.4
F-4	40	1 ³⁷ / ₆₄	120	4 ²³ / ₃₂	1,136	44 ²³ / ₃₂	12.0	26.4	87	3 ⁷ / ₁₆	1/2	12.7	1/2	0.85	30

Specifications are subject to change without notice.