

This vibrator is mounted on a hopper, tank, chute, etc. in a storage, conveying, drying crushing, or dust collecting system and gives vibrations to powder adhering to them to shake it down, thereby preventing them from clogging.

AIR CUSHION TYPE LOW SOUND LEVEL



NLV-1518AL



NLV-2125AL



NLV-2430BL



NLV-4856AL

- Lubrication free type: (NLV-1518AL, NLV-2125AL, NLV-2430BL)
- Silencer type

ROTARY TYPE



NRV-5223



NRV-30112

IMAPCT TYPE HIGH POWER



NLV-1518A



NLV-2125A



NLV-2430B



NLV-4856A



NLV-55



NLV-75A

- Lubrication free type: (NLV-1518A, NLV-2125A, NLV-2430B)
- Silencer type

SPECIFICATIONS

Type	Model No.	Vibration Per Minute		Height Approx.		Net Weight Approx.		Bolt Size		Bolt Pitch		Air Inlet Thread	Hose Size		Average Air Consumption		Recommended Air Pressure		
		min ⁻¹		mm	in	kg	lb	mm	in	mm	in		mm	in	m ³ /min	ft ³ /min	MPa	kgf/cm ²	psi
Air Cushion	NLV-1518AL	3,650		110	4 ^{11/32}	1.6	3.5	8	—	25	53/64	1/8	6.3	1/4	0.16	5.7	0.6	6	85
	NLV-2125AL	3,500		120	4 ^{23/32}	2.2	4.8	8	—	30	1 3/16	1/8	6.3	1/4	0.23	8.1	0.6	6	85
	NLV-2430BL	3,500		130	5 1/8	2.8	6.2	8	—	35	1 3/8	1/8	6.3	1/4	0.24	8.5	0.6	6	85
	NLV-4856AL	2,050		220	8 ^{21/32}	18.6	40.9	16	—	95	3 ^{25/32}	3/8	9.5	3/8	0.66	23.3	0.6	6	85
Impact	NLV-1518A	4,500		110	4 ^{11/32}	1.6	3.5	8	—	25	53/64	1/8	6.3	1/4	0.06	2.1	0.4	4	57
	NLV-2125A	4,350		120	4 ^{23/32}	2.2	4.8	8	—	30	1 3/16	1/8	6.3	1/4	0.07	2.5	0.4	4	57
	NLV-2430B	3,500		130	5 1/8	2.8	6.2	8	—	35	1 3/8	1/8	6.3	1/4	0.08	2.8	0.4	4	57
	NLV-4856A	2,100		220	8 ^{21/32}	18.7	41.4	16	—	95	3 ^{25/32}	3/8	9.5	3/8	0.39	13.8	0.4	4	57
	NLV-55	2,450		196	7 ^{23/32}	10.3	22.7	16	—	72	2 ^{27/32}	3/8	9.5	1/4	0.51	18.0	0.4	4	57
	NLV-75A	2,050		276	10 7/8	32.5	71.5	22	—	105	4 9/16	1/2	12.7	1/2	0.63	22.2	0.4	4	57
Rotary	NRV-30112	18,000		83	3 9/32	0.4	0.9	8	5/16	—	—	1/8	6.3	1/4	0.15	5.3	0.6	6	85
	NRV-5223	9,400		111	4 3/8	2.5	5.5	12	1/2	130	5 1/8	1/4	6.3	1/4	0.5	17.7	0.6	6	85

Specifications are subject to change without notice.